




Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h   4pole 4h   5pole 4h	3pole 6h   4pole 9h   5pole 9h	3pole 9h   4pole 6h   5pole 6h	3pole 7h   4pole 7h   5pole 7h	3pole 10h   4pole 10h   5pole 10h	3pole 2h   4pole 2h   5pole 2h		

**Part numbers**


	16	3	110 304	<b>110 306</b>	110 309				10/60	161
	16	3		110 306 AS = lockable with padlock (padlock is not included)						
	16	4	110 404	110 409	<b>110 406</b>	110 407	110 410	110 402	10	209
	16	5	110 504	110 509	<b>110</b>				10/60	227
	16	5			110 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					
	32	3	130 304	<b>130 306</b>	130 309				10	291
	32	4	130 404	130 409	<b>130 406</b>	130 407	130 410	130 402	10	300
	32	5	130 504	130 509	<b>130</b>				10/60	320
	32	5			130 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					


pic.130

**Wall sockets  IP 44, external fixing, 1 top cable entry**

	16	3	111 304	<b>111 306</b>	111 309				5	356
	16	4	111 404	111 409	<b>111 406</b>	111 407	111 410	111 402	5	389
	16	5	111 504	111 509	<b>111</b>				5	425
	16	5			111 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					
	32	3	131 304	<b>131 306</b>	131 309				5	426
	32	4	131 404	131 409	<b>131 406</b>	131 407	131 410	131 402	5	453
	32	5	131 504	131 509	<b>131</b>				5	489
	32	5			131 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					


pic.131

**Wall sockets  IP 44, internal fixing, 2 cable entries both, top and bottom**

	16	3		<b>114 306</b>					5	457
	16	3		<b>115 306</b> <sup>2)</sup>					5	467
	32	3		<b>134 306</b> <sup>3)</sup>					5	563
	32	3		<b>135 306</b> <sup>2)</sup>					5	595
	16	5			<b>114</b>				5	525
	16	5			<b>114 UV</b> <sup>1)</sup>				5	525
	16	5			<b>115</b> <sup>2)</sup>				5	537
	16	5			115 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					
	32	5			<b>134</b> <sup>3)</sup>				5	538
	32	5			<b>134 UV</b> <sup>1, 3)</sup>				5	538
32	5			<b>135</b> <sup>2)</sup>				5	619	


pic.132

**Mini combinations  IP 44, CEETyp wall socket with Schuko socket**

	63	3	161 304	<b>161 306</b>	161 309				1	825
	63	4	161 404	161 409	<b>161 406</b>	161 407	161 410	161 402	2	1046
	63	5	161 504	161 509	<b>161</b>				2	1105
	63	5			161 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)					

pic.161



**Wall sockets, internal fixing,  IP 44**

	63	3	163 304	<b>163 306</b>	163 309				1	1590
	63	4	163 404	163 409	<b>163 406</b>	163 407	163 410	163 402	2	1830
	63	5	163 504	163 509	<b>163</b>				2	1900


pic.163

**Wall sockets  IP 44, internal fixing, cable entries: 2 x top, 2 x bottom (knock-out)**





Ampère	Poles	110 V 50 a. 60 Hz			230 V 50 a. 60 Hz			400 V 50 a. 60 Hz			500 V 50 a. 60 Hz			> 50 - 500 V 100 - 300 Hz			> 50 - 500 V over 300 - 500 Hz				
		3pole 4h	4pole 4h	5pole 4h	3pole 6h	4pole 9h	5pole 9h	3pole 9h	4pole 6h	5pole 6h	3pole 7h	4pole 7h	5pole 7h	3pole 10h	4pole 10h	5pole 10h	3pole 2h	4pole 2h	5pole 2h		

**Part numbers**

	16	3	116 304	<b>116 306</b>	116 309													5	311	
	16	4	116 404	116 409	<b>116 406</b>		116 407		116 410		116 402							5	320	
	16	5	116 504	116 509	<b>116</b>													5	328	
	32	3	136 304	<b>136 306</b>	136 309														5	368
	32	4	136 404	136 409	<b>136 406</b>		136 407		136 410		136 402								5	370
	32	5	136 504	136 509	<b>136</b>														5	380

pic. 136


**mondo wall sockets IP 44** , surface mounting, RAL 7035 light grey

	32	3	436 304	436 306	436 309													10	361
	32	4	436 404	436 409	436 406		436 407		436 410		436 402							10	379
	32	5	436 504	436 509	436													10	389

pic. 436

To order a wall socket **with inscription label** please add „**BS**“ to the standard part no.  
To order a **lockable** wall socket **with inscription label** please add „**AS**“ to the standard part no.

**mondo wall sockets IP 44** , flush type, RAL 1013 pearl white, with flush-type socket


	16	3	117 304	<b>117 306</b>	117 309													10	187
--	----	---	---------	----------------	---------	--	--	--	--	--	--	--	--	--	--	--	--	----	-----

pic. 117306

**mondo wall sockets IP 44** , small version, surface mounting, RAL 7035 light grey


	16	3	418 304	<b>418 306</b>	418 309													10	155
---	----	---	---------	----------------	---------	--	--	--	--	--	--	--	--	--	--	--	--	----	-----

pic. 418306

**mondo wall sockets IP 44** , small version, flush-type, RAL 1013 pearl white


	16	2		<b>10 007</b>														10	153
---	----	---	--	---------------	--	--	--	--	--	--	--	--	--	--	--	--	--	----	-----

pic. 10007



**Earthing contact socket IP44** , **mondo** surface mounting wall socket, RAL7035 light grey

	16	2		<b>10 008</b>														10	120
---	----	---	--	---------------	--	--	--	--	--	--	--	--	--	--	--	--	--	----	-----

pic. 110306

**Schuko socket IP44** , **mondo** flush mounting wall socket, RAL1013 pearl white





Ampère	Poles	110 V 50 a. 60 Hz			230 V 50 a. 60 Hz			400 V 50 a. 60 Hz			500 V 50 a. 60 Hz			> 50 - 500 V 100 - 300 Hz			> 50 - 500 V over 300 - 500 Hz				
		3pole 4h	4pole 4h	5pole 4h	3pole 6h	4pole 9h	5pole 9h	3pole 9h	4pole 6h	5pole 6h	3pole 7h	4pole 7h	5pole 7h	3pole 10h	4pole 10h	5pole 10h	3pole 2h	4pole 2h	5pole 2h		

**Part numbers**




pic. 139

	16	3	119 304	<b>119 306</b>	119 309														5	409
	16	4	119 404	119 409	<b>119 406</b>	119 407		119 410		119 402									5	440
	16	5	119 504	119 509	<b>119</b>														5	470
	32	3	139 304	<b>139 306</b>	139 309														5	492
	32	4	139 404	139 409	<b>139 406</b>	139 407		139 410		139 402									5	492
	32	5	139 504	139 509	<b>139</b>														5	551
	139 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)																			

**Wall sockets  IP 67, internal fixing, 2 knock-out cable entries both, top and bottom**




pic. 168

	63	3	168 304	<b>168 306</b>	168 309														2	1600
	63	4	168 404	168 409	<b>168 406</b>	168 407		168 410		168 402									2	1930
	63	5	168 504	168 509	<b>168</b>														2	2000

**Wall sockets  IP 67, internal fixing, cable entries: 2 x top, 2 x bottom (knock-out)**




pic. 169


	63	3	169 304	<b>169 306</b>	169 309														2	865
	63	4	169 404	169 409	<b>169 406</b>	169 407		169 410		169 402									2	1086
	63	5	169 504	169 509	<b>169</b>														2	1148
	169 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)																			

**Wall sockets  IP 67, internal fixing**




pic. 178

	125	3	178 304	<b>178 306</b>	178 309														1	2540
	125	4	178 404	178 409	<b>178 406</b>	178 407		178 410		178 402									1	3180
	125	5	178 504	178 509	<b>178</b>														1	3890
	125	3	178 304 OK	<b>178 306 OK</b>	178 309 OK	(OK = without terminal block)													1	1970

**Wall sockets with multi contacts  IP 67, internal fixing, with terminal block 5 x 50 mm<sup>2</sup>**



pic. 179

	125	3	179 304	<b>179 306</b>	179 309														1	2720	
	125	4	179 404	179 409	<b>179 406</b>	179 407		179 410		179 402									1	3260	
	125	5	179 504	179 509	<b>179</b>														1	3800	
	179 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)																				
	125	3	179 304 OK	<b>179 306 OK</b>	179 309 OK															1	1170
	125	4	179 404 OK	179 409 OK	<b>179 406 OK</b>	179 407 OK		179 410 OK		179 402 OK										1	1710
	125	5	179 504 OK	179 509 OK	<b>179 OK</b>	(OK = without terminal block)													1	2250	

**Wall sockets with multi contacts  IP 67, internal fixing, with terminal block 5 x 50 mm<sup>2</sup>**